Flexible Whip

AFB

17/10/2014 V1




- Flexible whip
- Removable for car wash
- UHF frequency


This antenna features a flexible construction within a black nylon tube. This provides damage resistance without compromising RF performance.

The Panorama mounting system provides a high degree of interchangeability between whips and bases, making them suitable for all applications whether temporary or permanent.


The AFB range is suitable for use with all Panorama GPS combination and light duty magnetic bases.

Technical Drawing





VSWR shown on a 1x1m (3'x3') ground plane with 5m of CS23 (RG58 c/u) cable



Part No.					
		AFB-S1	AFB-S2	AFB-TET	AFB-S4
Electrical Data	ı.				
Frequency Range (MHz)		380-400	310-430	380-430	450-470
Gain: Isotropic		2dBi			
Compared to 1/4 wave		OdB			
Polarisation		Vertical			
Pattern		Omni-directional			
Impedance		50Ω			
Max Input Power (W)		100			
Mechanical Da	ata				
Dimensions (mm)	Height	158 (6.2")	148 (5.8")	154 (6.1")	130 (5.1")
	Diameter	10(0.4")			
Operating Temp (°C)		-40° / +80°C (-40° / 176°F)			
Material		Stranded speedo cable & Nylon			
Colour		Black			
Mounting Data	a				
Fixing		M6 x 0.75 (GPSB, GPSK & MAR bases)			



Frogmore, London, SW18 1HF, United Kingdom

T: +44 (0)20 8877 4444 F: +44 (0)20 8877 4477

E: sales@panorama-antennas.com

www.panorama-antennas.com

Waiver: The data given above is indicative of the performance of the product/s under particular conditions and does not imply a guarantee of performance. These specifica-

tions are subject to change without notice.

Copyright © Panorama Antennas Ltd. All rights reserved.