





ANTENNA MOULDED
OVER IN BLACK
ENGINEERING PLASTIC

5m LONG COAX
CABLE Ø5mm

FME JACK

ADHESIVE PAD

Ø6.0 IN.
4 POSN'S

OPERATING FREQUENCIES :-
698 - 960MHz.
1710 - 2700MHz.

NOTES:

1. SAMPLES MUST BE APPROVED BY PANORAMA ANTENNAS Q.C. BEFORE COMMENCING PRODUCTION.
2. ALL MATERIALS SUPPLIED MUST BE RoHS2 (DIRECTIVE 2011/65/EU) COMPLIANT AND MUST NOT CONTAIN ANY SUBSTANCES OF VERY HIGH CONCERN (SVHCs) LISTED UNDER REACH OR POLY-AROMATIC HYDROCARBONS (PAHs), OR PERSISTENT ORGANIC POLLUTANTS (POPs) CONTROLLED BY THE STOCKHOLM CONVENTION.

DRG. No. BMP1-7-27-5F		SHEET 2 OF 2	
PRODUCT/ASSEMBLY COVERT ANTENNAS			
DESCRIPTION MULTI-BAND BUMPER ANTENNA SINGLE ELEMENT 5m FME JACK			
MATERIAL N/A			
FINISH N/A			
WEIGHT N/A			
APPROVED		DO.CHECK AR	
SCALE 1:1		DIMENSIONS IN mm	
DO NOT SCALE	3RD ANGLE PROJECTION		
01019	1	PRODUCTION ISSUE	14/09/2016 IC
PCN	REV.	DESCRIPTION	DATE DRN
TOLERANCES UNLESS OTHERWISE STATED			
0 DEC. PLACE ±0.5		2 DEC. PLACES ±0.1	
1 DEC. PLACE ±0.2		ANGULAR ±1°	
	DENOTES LATEST ISSUE CHANGES		
		DENOTES CRITICAL VALUE	
THIS DOCUMENT MUST NOT BE COPIED OR DISCLOSED TO A THIRD PARTY WITHOUT THE WRITTEN CONSENT OF PANORAMA ANTENNAS LTD.			
© 2016		A4	