Γ		1		2			3			4			5	6	
	-	3RD ANGLE DO NOT PROJECTION SCALE		ENOTES LATEST			S CRITICAL	© 2017 A4	THIS DOC WITHOUT	UMENT MUST	NOT BE COPIED OR D	NSCLOSED TO A THIRD PA RAMA ANTENNAS LTD.	RTY DRG. No.	C23FP-5SP-GNSS	
	0	OLERANCES UNLESS OTHERWISE STATED       DEC. PLACE     ±0.5     2 DEC. PLACES     ±0.1       DEC. PLACE     ±0.2     ANGULAR     ±1°		CABLE SPECIFICATION VALUES:- 1. CHARACTERISTIC IMPEDANCE:- GENERAL NOTES:-											
ŀ	•		1.	50Ω ±2Ω @ 1GHz 50Ω ±4Ω @ 2GHz								ALL MATERIALS SUPPLIED MUST BE RoHS2 (DIRECTIVE 2011/65/EU) COMPLIANT AND MUST NOT CONTAIN ANY SUBSTANCES OF VERY HIGH CONCERN (SVHCs)			
			2.	ATTENUA NO GREA NO GREA	FER TH							LISTED UNDER REACH OR POLY-AROMATIC HYDROCARBONS (PAHs), OR PERSISTENT ORGANIC POLLUTANTS (POPs) CONTROLLED BY THE STOCKHOLM CONVENTION.			
			3.	MAX. PEA	K VOLT	AGE:- 1	1.5kV D	C.			2.		H TO BE BI	ACK, UV STABILISED PACREL	
			4.	BRAID RE	SISTAN	CE PER	R 10m L	ESS THAN 16	0mΩ.			6385N TPE.		ACK, UV STADIEISED FACILE	
			5.	SHIELDING 55dB AT 3			NESS A	CCORDING TO	D IEC611	96 TO E		PRINTING MU RESISTANT.	ST BE DURA	ABLE AND ENVIRONMENTALLY	
E	3		SPE	CIFICATION	NOTES	8:						CONNECTOR: INTERFACE D		NFORM TO STANDARD	
			1.		ONDU	CTOR/C	DUTER	LE. SCREEN ISOL END TEST.	ATION 1	KV MIN	. 5.	SAMPLES MU	ST BE APPR	OVED BY PANORAMA COMMENCING PRODUCTION.	
_	2. TENSILE PULL TEST SAMPLE/ASSEMBLY PER 3000 BATCH. PULLING LOAD - CONNECTOR BODY - 5Kg. PULLING LOAD - CENTRE PIN - 2Kg. PULLING LOAD - 2KG. PULLI										ION 1502) TIN, GOLD, CONTAINED IN PANORAMA				
			<ol> <li>CS23 CABLE PERFORMANCE TEST SAMPLE PER 10000 m BATCH.</li> <li>IMPEDANCE 50Ω ±2Ω @ 1GHz. &amp; 50Ω ±4Ω @ 2GHz.</li> <li>LOSS NO GREATER THAN 0.5dB/m @ 1GHz. &amp; 0.75dB/m @ 2GHz.</li> </ol>									THE CONFLICT FREE			
0	C $(10)$											_1			
		(30) (30) (10) (30) (10) (30) (10) (30) (10) (30) (10)													
			GPS/G		W.PAI	NORA	MA-A	NTENNAS.	СОМ	- CS	23 - LO	W LOSS	GPS/GNSS		
		WWW.PANORAMA-ANTENNAS.COM - CS23 - LOW LOSS													
		SMA PLUG HEAT SHRINK FITTED. HEAT SHRINK SLEEVE 2 POSITIONS FITTED IN WHITE ON SHEATH AT REGULAR INTERVALS FITTED. FITTED.													
[												MBLY AND CABLE EMBLIES		IG FITTED- SMA PLUG FITTED S23 CABLE ASSEMBLY	
												N/A			
						01019		PRODUCTION ISSUE	12/1	2/2017 10	FINISH	N/A		O.CHECK MM SCALE DIMENSIONS IN mm	
						01019	2	CONFIGURATION UPDA CHANGES)	15/1	2/2017			PANOR	a m a 🧭 a n t e n n a s	
L						PCN	REV.	DESCRIPTION	[	DATE DF	RN. WEIGHT 201g	SHEET 1 OF 1			